

CARTRIDGE FILTRATION PF-400

- Operating pressures up to 75 PSI
- Flow rates up to 400 GPM



FEATURES

- Dual bag and cartridge filtration.
- 4 bag filters for high solids holding capacity.
- 2 cartridge chambers for high solids removal efficiency.
- Replaceable cartridges available in a range of .5 to 100 micron nominal rating.
- Manifold valving for ease of use.
- Isolation valving.
- No moving parts.
- Skid mounted unit.
- Loading platform
- Units fitted with bleed valves and pressure gauges.

TECHNICAL

- Initial pressure drop is less than 5 psi at 500 gpm.
- System can stand alone for sediment removal or be used in combination with media vessels.
- Multiple cartridge filters provide large surface area for longer service life.

MATERIAL SPECIFICATIONS

- Chambers constructed out of 304 stainless steel.
- 3" victaulic inlet and outlet.
- Each bag filter chamber holds one 7" x 20" double stitched filter bag.
- Each cartridge chamber holds twelve 40" long double open-ended cartridges with 2-1/2" OD and 1" ID.
- Maximum operating temperature 200° F.
- Maximum operating pressure 75 PSI.



Clear Creek Systems

Nationwide Service
CA • MD • OR • WA
Phone • 877 324 9634
sales@clearcreeksystems.com
www.clearcreeksystems.com